

# GHOST

Quick Installation Guide



# Box Contents

- **Ghost Case**
- **Ghost Quick Installation Guide**

## ○ Accessories:

- ⊖ Cable Management Grommets: x 4
- ⊖ PSU Anti-vibration standoffs: x 4
- ⊖ 3.5" HDD Trays: x 4
- ⊖ 2.5" HDD/SSD Trays: x 3
- ⊖ SATA 6Gb/s Connector Cover: x 1

## ○ Screws:


- ⊖ Standard Screw 6-32 Flat: x 16 (For MB, PSU & 3.5" HDD)
- ⊖ Standard Screw M3\*5mm Round: x 6 (For FDD & 5.25" ODD)
- ⊖ Standard Screw M3 Mini: x 16 (For SSD & 2.5" HDD)
- ⊖ Long fan screws: x 4 (For Front Fans)
- ⊖ Thumbscrews 6-32: x 7 (For PCI )
- ⊖ Motherboard Standoffs: x 2 (For MB)

\* Contents and specifications subject to change without notice.







**Front**



**Top**




**Back**




**Side**

## Basic Installation

### Removing side panels




a. Remove thumbscrews




b. Remove side panels


## Installing 5.25" drives




a. Open front door or remove it if necessary (please remove hinge clips before removing front door)



b. Squeeze and pull to remove hinge clips




c. Remove ODD bay cover by pushing tabs from inside chassis




d. Slide drive into drive bay




## Installing 3.5" drives



a. Remove hard disk tray




b. Install drive by bending rails of tray to the side




c. Slide tray into place


## Installing 2.5" drives



a. Remove hard disk tray




b. Install drive by bending rails of tray to the side



c. Slide tray into place

## Features

### Control Panel



**A. Headphone jack**

**B. Microphone jack**


**C. USB2.0 ports**

**D. SuperSpeed USB3.0 ports**


**E. Power button**

**F. Reset button**


## Top Fan Installation (120mm)




a. Remove top filter by pressing down the two rear corners



b. Install fans




c. Secure with screws




d. Replace top filter




# Front Fan Installation




a. Open front door or remove it if necessary (please remove hinge clips before removing front door)




b. Remove front filter by pressing down the two left corners



c. Release front panel clips by gently pulling on front panel



d. Install fans




e. Secure with long fan screws






## Rear Fan Installation




a. Install fan




b. Secure with screws

## Bottom Fan Installation




a. Install fan




b. Secure with screws


## Moving HDD wall




a. Remove screws from HDD cage



b. Pull to remove




c. Slide HDD wall in to place




d. Secure with screws


## Using S4™



a. Open by pressing down the lid




b. Remove hotswap cover




c. Slide HDD into place

## LED-Strip Installation




a. Stick LED-strips into place



b. Pull 2-pin connector through chassis bottom holes

# Filters





**BITFENIX**

**Bitfenix Co., Ltd.**

3F, No.79, Sec. 1, Xintai 5th Rd.,

Xi Zhi District, New Taipei City, Taiwan, R.O.C.

For the most updated information, please visit our official website: <http://www.bitfenix.com>

© 2012 BITFENIX Co., Ltd. All Rights Reserved. All trademarks are registered to their respective owners.

Ver 1.0 : 2012/06